

CP- DNW-HP4H2-6**6 Port Fast Ethernet Switch with 4 PoE****Main Features**

- 4, 10/100Mbps; RJ45 ports; Max. 30W Output of Single PoE Port
- Support IEEE802.3/802.3u/802.3ab/802.3z/802.3x
- 2, 100Mbps; Transmission Distance: 0-100m

CP- DNW-HP4H2-6**6 Port Fast Ethernet Switch with 4 PoE****Feature**

Uplink Ports
Network Standard
Switch Capacity
Packet Forwarding Rate

PoE Ports

Network Ports
Transmission Distance
MAC Address List
PoE Standard
PoE Power Supply
PoE Power Budget
Ethernet Port Light
Surge Protection
Forwarding Mode
Power Source
Operating Temperature
Power Consumption
Storage Temperature
ESD
Anti-thunder Level
Humidity
Dimensions
Color
Warranty

Specification

2, 100Mbps; Transmission Distance: 0-100m
IEEE802.3/802.3u/802.3ab/802.3z/802.3x
1.6Gbps
1.15Mpps

4, 10/100Mbps; RJ45 ports; Max. 30W Output of Single PoE Port
Transmission distance: 0~100/250M(the extend distance is adjusted by the switch)

6
Default: 0-100/250M (the extend distance is adjusted by the code switch)
1k
IEEE802.3af, IEEE802.3at
1/2(+),3/6(-)
60W
2pcs(Yellow & Green) on RJ45, Green indicates PoE, Yellow indicates Link Act
6KV
Store-and-forward
Built-in Power Supply, Input: 100-240V AC, 50/60Hz
-10°C~-45°C
<5W
-40°C~85°C
Contact Discharge 6KV / Air Discharge Level 8KV
6KV, Standard: IEC61000 4 5
5%-95% , non-condensity
200mm x 145mm x 44mm
Black
2 Years